



CONVERSION HOIST VP-6/VC-6

For Standard Pickup Trucks
Platform and Dump Body Applications

*For Standard Full Size Pickups
VP6R - Chevrolet, GMC, Ford
VP6D - Dodge*

- *6000-Pound Capacity*
- *45° Dumping Angle*
- *Factory Assembled*
- *No Welding Of Truck Frame Or Pickup Body*



**Specify Make, Model And Year When Ordering*



Your choice of:

- *Single and Double Acting Models Include in Cab Dashboard Electronic Controls—Eliminates Problems Associated with Cable Controls*
- *Bumper Mounting Kits*
(Recommended Option)
- *Longitudinal Body Supports*
(Recommended Option)
- *Body Prop*
(Recommended Option)

For Dumps and Platforms:

- *VC Model features upper pivot and rear hinge assembly for bodies with longills (Specify "VC" when ordering)*



SPECIFICATIONS

- 3 1/2" diameter cylinder, 13" stroke operating at 2400 P.S.I.
- Factory assembled variable width mounting base adapts to original crossmember.
- One piece unitized upper nest insures maximum support to pickup body.
- Built-in tapered guides standard.
- Heavy Duty 12 volt electric hydraulic Single-acting and Double-acting pumps.
- Double-acting option operates at 650 P.S.I. down pressure.

FEATURES

- Completely assembled and tested at factory - eliminates parts shortages and speeds installation.
- Most installations completed in 6-8 hours.
- Exclusive Double-acting feature assists the pickup down and holds it down, preventing pickup body vibrations (nylon noise reducer mounting pads standard on all models).
- 1/4" - 3/4" mounting height permits cab and pickup body to retain original style lines (See Photograph).
- In-cab dashboard electronic controls standard.
- Venco optional bumper brackets allow for installation of pickup bumper and hitch (class II).
- Venco optional longitudinal body supports.

A Product of:



VENCO MANUFACTURING, INC

A DIVISION OF COLLINS ASSOCIATES, INC.

12110 BEST PLACE
CINCINNATI, OH 45241
PHONE: 800-226-2238
FAX: 513-326-5427

www.venturo.com

e-mail: sales@venturo.com

Distributed By:

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE