

- Fits platforms 14'-24'
Dumps 10'- 18'
- Capacities up to
78,200 lbs.
- Available with single or
twin 6" cylinder(s) and
28" stroke.
- Choice of piston or
direct mount PTO
pumps. Electric pump
available for VC628.
- Completely assembled
at factory to eliminate
parts shortages and
speed installation.
- Low mount design for
greater stability.
- Unitized quick mount
hinge assembly.



Single safety prop installed on the main frame of hoist is standard. Second body prop as shown is optional on VC628 and standard on VC6628.

SPECIFICATIONS

VC628

VC6628

- Conversion class F
- Dump class 60
- Single high pressure cylinder with 6" bore x 28" stroke and multi-hard chromed and polished piston rod.
- Mounting height 8"
- 8 piston double acting pump with 21 qt. reservoir. Direct mount gear pump and electric pump also available.
- Operating pressure 3000/1000 psi.
- Weight 825 lbs.

- Conversion class J
- Dump class 90
- Twin high pressure cylinders with 6" bore x 28" stroke and multi-hard chromed and polished piston rod.
- Mounting height 10.5"
- 8 piston double acting pump with 27 qt. reservoir. Direct mount gear pump also available.
- Operating pressure 3000/1000 psi.
- Weight 1190 lbs.

Body Length	C/A	C/T	Rear Overhang	Capacity (tons) 45° Dump	Capacity (tons) 50° Dump
14'	102"	-	36"	20.8	19.2
14'	108"	-	30"	18.5	17.1
14'	120"	108"	18"	15.2	14.0
16'	120"	108"	42"	18.5	17.1
16'	138"	126"	24"	13.9	12.8
16'	156"	144"	6"	11.1	10.3
18'	138"	126"	48"	16.7	15.4
18'	156"	144"	30"	12.8	11.8
18'	168"	156"	18"	11.1	10.3
MOUNTING DISTANCE				130.5"	118.25"

Body Length	C/A	C/T	Rear Overhang	Capacity (tons) 45° Dump	Capacity (tons) 50° Dump
18'	138"	126"	48"	35.7	32.4
18'	150"	138"	36"	29.7	27.0
18'	168"	156"	18"	23.8	21.6
20'	168"	156"	42"	27.4	24.9
20'	180"	168"	30"	23.8	21.6
20'	192"	180"	18"	21.0	19.0
22'	186"	174"	48"	25.5	23.1
22'	-	192"	30"	21.0	19.0
24'	-	198"	48"	22.3	20.2
24'	-	216"	30"	18.8	17.0

Body Length	Rear Overhang	Capacity (tons) 50° Dump
10'	12"	19.1
12'	12"	15.3

Body Length	Rear Overhang	Capacity (tons) 50° Dump
12'	12"	32.4
13'	12"	29.4
14'	12"	27
15'	12"	24.9
16'	12"	23.1
18'	12"	20.2

ONE YEAR WARRANTY

For one year from date of original purchase, we will replace or repair free of charge all Venco parts returned to our factory prepaid and found upon inspection by us to be faulty due to defects in materials or workmanship. We shall not be liable for any contingent liabilities arising out of the improper function of any parts. We make no warranty with respect to parts not of our manufacture, but we will carry out the terms of the warranties of their respective manufacturers. One year warranty on hydraulic cylinders including labor.

WARNING - These products are not passenger lifts. They are not designed or intended to be used to lift, support or otherwise transport personnel. It is the responsibility of the installer to not only insure that the installation is completed accordingly to the manufacturer's recommendations, but to insure that the ultimate user understands how to operate in a safe manner and the need for regular service and maintenance by an authorized Venco distributor. No modifications or alterations may be made to any Venco equipment without the expressed written consent of the manufacture. Reinstallation of any Venco product must be done by an authorized Venco distributor to the standards of the industry, including the maintenance and service and the affixing of all safety and warning labels. Users should again be instructed as to the safe operation at time of delivery. Maintenance, service, operation and safety warning decals are available on request from Venco Mfgr, Inc.

A Product Of:



MANUFACTURING, INC.

12110 BEST PLACE
CINCINNATI, OHIO 45241
PHONE: (800) 226-2238
FAX: (513) 326-5427

Distributed By: