



ET8KX



Capacity	3200 lbs
Crane Rating	8000 ft.lbs.
Boom Length(s)	6' - 14'
	6' - 10' Power
	10' - 14' Manual
Min. GVWR	Class 2 - 8000 lbs
Controls	12V DC

Specifications

Capacity	3200 lbs
Crane Rating	8000 ft.lbs.
Boom Length(s)	6'3" - 10'5" - 14'2"
	6'3" - 10'5" Power Boom
	10'5" - 14'2" Manual Boom
Stowed Boom Length	7'7-3/8"
Dimensions	26-7/8" H x 18-1/5" W
Base Plate	14" x 14"
Bolt Holes	12" x 12" (4x - Ø5/8")
Swing Radius	R14-5/8"
Wire Rope	65 ft. of 1/4"
Crane Weight	650 lbs

Battery Requirements

Cold Cranking Amps (0° F)	625
Reserve Capacity (min. @ 80° F)	160

Minimum Wire Gauge per FT of Cable

0-20 FT	#2
21-25 FT	#2
26-30 FT	#1
31-40 FT	#0
41-50 FT	#00

Min. Circuit Breaker Kit	250 AMP
Rotation	360-Degrees
Power	12V DC

Standard Equipment

#2 Gauge x 5' Black Grounding Strip
#2 Gauge x 5' Red +12V Battery Cable
Master Disconnect Switch Kit
#2 Gauge x 26' Battery Cable
Non-Proportional Controls
25 FT Plug-In Remote-Control Pendant
Anti-Two Blocking
Master Disconnect Switch Kit and Bracket
Swivel Load Block with Safety Hook

Optional Equipment

Wireless Radio Remote
Proportional Controls
Capacity Overload Alarm
21" High Mounting Pedestal
36" High Mounting Pedestal
Adjustable 13" - 19" Boom Rest
250 AMP Circuit Breaker Kit
Custom Paint
Full, Rear Crankdown Outrigger Package
Jackleg for Utility Bodies
Jackleg for Flatbed Bodies



Venco Venturo Industries LLC
12110 Best Place | Cincinnati, Ohio 45241
800-226-2238 | 513-772-8448 Local
info@venturo.com | www.venturo.com

NOTE: All Venturo service cranes meet ANSI B30.5 and OSHA 1910.180 specifications. Specifications subject to change without notice.
Copyright © 2022 Venco Venturo Industries LLC. All Rights Reserved.



ET8KX

