



CONVERSION DUMP HOISTS VC6620



CAPACITY RANGE
17 - 39 TON

BODY LENGTHS
14 - 20 FT

CONV. CLASS
G

DUMP CLASS
70

TRUCK FRAME
34"

FEATURES

■ VARIETY OF POWER OPTIONS

The VC6620 can be fit with our DM (Direct-Mount PTO Driven) or LDK (Less Drive Kit - No power or hoses).

■ UPDATED DESIGN

Low-mounting height scissors design with narrow drop-hinge knuckle.

RELIABILITY & QUALITY

Since 1981, Venco's underbody hoists are highly regarded in the industry and represent an excellent value. Venco offers a full line of underbody hoists designed for use with bodies ranging in lengths from 14" to 20" long, providing dumping capacities of 17 to 39 tons. Venco hoists are encapsulated in a durable abrasive and chemical resistant powder coating. When you purchase an underbody hoist from Venco, all necessary mounting hardware, fasteners, and body prop hardware are included. Venco hoists are covered under a 3 year product warranty.

SPECIFICATIONS

Lifting Capacities:	17 - 39TONS
Body Length:	14 - 20 FT
Cylinder:	Twin 6"
Stroke:	20"
Conversion Class:	G
Dump Class:	70
Mounting Height:	8-1/2"
Operation Pressure:	3000/1000 PSI
CA	84" - 156"
DM Power Supply:	PTO
Hydraulic Req:	PTO - 21 qt. reservoir
Weight: VC6620:	965 LBS
PTO Pump:	SAE "B" 2-bolt flange, 7/8" - 13 Spline (Bi-Rot.) w/ 21 qt. reservoir

MAXIMUM LOAD CAPACITY CHART

14'	108"	30°	34.8	30.9	29.3
14'	114"	24°	31.3	27.8	26.4
14'	132"	6°	24.1	21.4	20.3
15'	114"	36°	34.8	30.9	29.3
15'	124"	26°	29.4	26.1	24.7
15'	132"	18°	26.1	23.2	22.0
15'	150"	0°	20.9	18.5	17.6
16'	108"	54°	44.8	39.7	37.7
16'	114"	48°	39.2	34.8	33.0
16'	120"	42°	34.8	30.9	29.3
16'	124"	38°	32.4	28.8	27.3
16'	132"	30°	28.5	25.3	24.0
16'	138"	24°	26.1	23.2	22.0
18'	138"	48°	31.3	27.8	26.4
18'	144"	42°	28.5	25.3	24.0
18'	150"	36°	26.1	23.2	22.0
20'	150"	60°	31.3	27.8	26.4
20'	156"	54°	28.5	25.3	24.0

DUMP BODY APPLICATIONS VC6620 *					
BODY	CA	O.H.	40° (TON)	45° (TON)	50° (TON)
11'	-	12"	-	-	29.3
12'	-	12"	-	-	26.4
13'	-	12"	-	-	24.4
14'	-	12"	-	-	22.0

DM/LDK KITS

(DM) DIRECT-MOUNT PTO DRIVEN

- Power-Up, Power Down
- Pump: SAE "B" 2-bolt Flange, 7/8" - 13 Spline Shaft Bi-Rotational (21 qt reservoir)
- Includes Hoses, Controls, Hydraulic Fittings

(LDK) LESS DRIVE KIT

- **INCLUDES:** Mounting Kit, Rear Hinges & Scissors with Cylinder
- **DOES NOT INCLUDE:** Hoses, Controls, Hydraulic Fittings, Pump & Tank Combo

