

ELECTRIC CRANES

CT2000 SERIES



SPECIFICATIONS

Lifting Capacities:	1,500 lbs 2,000 lbs
Crane Rating:	6,000 ft-lbs
Mounting Space:	10" x 10" Mounting Plate ("A" or "C" sockets)
Stowed Height:	71-3/4"
Rope Diameter:	3/16" @ 35' (75' optional)
Max. Single-line:	950 lbs
Max. Double-line:	2,000 lbs
Rotation:	360° Manual Rotation w/ 8 Position Positive Pin Lock
Power Supply Requirements:	12V DC Heavy-Duty Motor
Hydraulic Req:	No hydraulics
Boom Elevation:	3-position (20°, 40°, 60°)
Controls:	12V DC On/Off Winch (Option): 12V DC Proportional Hyd
Boom Extension:	3' - 5' 4' - 7'
Weight:	235lbs 265lbs
Minimum Vehicle Class:	1 Ton
Optional:	Tall Mast or Short Mast



The CT2000 series cranes include the Venturo CT2003FB and CT2004FB models. The Venturo CT2003FB and CT2004FB include a heavy-duty electric winch (1.8 hp) with manual rotation, manual extension, and a folding boom.

FEATURES

- **FRICTIONLESS MANUAL ROTATION**
Manual 360-degree rotation with a band brake provides unlimited, easy-to-use controlled load positioning.
- **POWERFUL 12V DC ELECTRIC WINCH**
ET Series winches combine a powerful permanent magnet DC motor with robust sealing and a proven 3-stage, all-metal gear train. Permanent grease lubrication provides years
- **MULTI-CONFIGURATION OPTIONS**
Custom cut-down of Mast height and multiple boom length options to fit a wide range of applications

