

## ELECTRIC - HYDRAULIC CRANES

### 4016E (ET16KX-16)

#### SPECIFICATIONS

<b>Lifting Capacities:</b>	4,000 lbs
<b>Crane Rating:</b>	16,000 ft-lbs
<b>Mounting Space:</b>	13-1/2" x 17-3/8"
<b>Stowed Height:</b>	29.6"
<b>Rope Diameter:</b>	5/16" @ 80'
<b>Line Pull Speed</b>	25 ft/min (Single-line) 4 ft/min (Double-line)
<b>Max. Single-line:</b>	2,000 lbs
<b>Max. Double-line:</b>	4,000 lbs
<b>Rotation:</b>	360° Continuous
<b>Power Supply Requirements:</b>	<b>Power Supply:</b> Electric 12V DC <b>Requirements:</b> 12v DC Battery
<b>Hydraulic Req:</b>	Self-Contained w/ Power Unit
<b>Boom Elevation:</b>	-5° to +75°
<b>Controls:</b>	Electric On/Off Functions
<b>Hydraulic Power</b>	Elevation/ Rotation/ Extension
<b>Boom Extension:</b>	Power: 8' - 12' Manual: 12' - 16'
<b>Weight:</b>	900 lbs
<b>Minimum Vehicle Class:</b>	Class 3 (10,500 lbs GVWR)
<b>Optional:</b>	- Proportional - Non-Proportional - Corded - Corded & Wireless

\*Venturo Body: VP16 Crane  
Service Body



The Ventura 4016E is a 16,000 ft-lb electric-hydraulic service crane with a 4,000 lb maximum capacity. This crane allows operators a crane application without the need for a heavy crane service body. A reinforced crane compartment on a standard utility body provides operators the strength they need on a standard service truck.

#### FEATURES

- **INDUSTRY LEADING IN ELECTRIC-HYDRAULIC CRANES**
- **POWERFUL DC ELECTRIC WINCH**  
The ET series winches combine a powerful permanent magnet DC motor with robust sealing with proven 3-stage, all-metal gear train. Permanent grease lubrication means years of trouble-free service.
- **MANUAL CRANE OVERRIDE**  
Each ET series crane gives the user the ability to operate and stow the crane if there is power loss through the remote
- **POWERFUL HYDRAULIC SLEW DRIVE**  
Driven from high quality durable electric motor
- **COUNTER-BALANCE VALVE**  
Counterbalance valving in all cylinders for increase safety and protection during operation

MAXIMUM LOAD CAPACITY CHART

