

## ELECTRIC - HYDRAULIC CRANES

### 4516E (ET18KX-16)

#### SPECIFICATIONS

<b>Lifting Capacities:</b>	4,500 lbs
<b>Crane Rating:</b>	18,000 ft-lbs
<b>Mounting Space:</b>	13-1/2" x 17-3/8"
<b>Stowed Height:</b>	29.6"
<b>Rope Diameter:</b>	5/16" @ 80'
<b>Line Pull Speed</b>	25 ft/min (Single-line) 4 ft/min (Double-line)
<b>Max. Single-line:</b>	2,250 lbs
<b>Max. Double-line:</b>	4,500 lbs
<b>Rotation:</b>	360° Continuous
<b>Power Supply Requirements:</b>	<b>Power Supply:</b> Electric 12V DC <b>Requirements:</b> 12v DC Battery
<b>Hydraulic Req:</b>	Self-Contained w/ Power Unit
<b>Boom Elevation:</b>	-5° to +75°
<b>Controls:</b>	Electric On/Off Functions
<b>Boom Extension:</b>	Power: 8' - 12' Manual: 12' - 16'
<b>Weight:</b>	900 lbs
<b>Minimum Vehicle Class:</b>	Class 3 (10,500 lbs GVWR)
<b>Optional:</b>	- Non- Proportional - Proportional - Corded - Corded & Wireless

\*Venturo Body: VP40 & VP45  
Crane Service Body



The Venturo 4516E is an 18,000 ft-lb electric-hydraulic service crane with a 4,500 lb maximum capacity. This crane gives operators the distance and strength they need for lighter crane service bodies. Large enough to pull heavy equipment, docks or any other loads at a shorter distance with a large capacity, the crane is also small enough for a mid-size GVWR truck.

#### FEATURES

- **INDUSTRY LEADING IN ELECTRIC-HYDRAULIC CRANES**
- **POWERFUL DC ELECTRIC WINCH**  
The ET series winches combine a powerful permanent magnet DC motor with robust sealing with proven 3-stage, all-metal gear train. Permanent grease lubrication means years of trouble-free service.
- **MANUAL CRANE OVERRIDE**  
Each ET series crane gives the user the ability to operate and stow the crane if there is power loss through the remote
- **POWERFUL HYDRAULIC SLEW DRIVE**  
Driven from high quality durable electric motor
- **COUNTER-BALANCE VALVE**  
Counterbalance valving in all cylinders for increase safety and protection during operation

MAXIMUM LOAD CAPACITY CHART

