ELECTRIC

CE6K

SPECIFICATIONS

Lifting Capacities: 2,000 lbs

Crane Rating: 6,000 ft-lbs

Mounting Space: 10" x 10"

Stowed Height: 61-1/8"

3/16" @ 60' Rope Diameter:

24.3 ft/min Line Pull Speed (Single-line)

Max. Single-line: 1,000 lbs

Max. Double-line: 2,000 lbs

Manual with **Rotation:** Band Brake

Power Supply:

Electric 12V

DC Power Supply

Requirements: Requirements:

> 12v DC Battery

Hydraulic Req: No hydraulics

3-position **Boom Elevation:**

(20°, 40°, 60°)

12V DC On/ **Controls:**

Off Winch

Manual: 3' - 5'

Boom Extension:

Manual: 4' - 7'

247lb Weight:

265lbs

Minimum Vehicle

Class:

No minimum

-Tall Mast or **Optional:**

Short Mast





The CE6K is a 2,000 lb. crane and is available with your choice of boom sizes and mast heights to meet a variety of lifting needs. This crane features an electric 12V DC winch, manual rotation, manual extension, and manual elevation.

FEATURES

FRICTIONLESS MANUAL ROTATION

Manual 360-degree rotation with a band brake provides unlimited, easy-to-use controlled load positioning.

POWERFUL 12V DC ELECTRIC WINCH

ET Series winches combine a powerful permanent magnet DC motor with robust sealing and a proven 3-stage, all-metal gear train. Permanent grease lubrication provides years

MULTI-CONFIGURATION OPTIONS

Custom cut-down of Mast height and multiple boom length options to fit a wide range of applications

