VC520

VENCO

For handling small- and mediumsized jobs, the VC520 is a rugged, reliable choice. Rated at NTEA class D/40, this hoist fits 12-15ft lengths with a compact 8–18-ton capacity range. Every Venco underbody hoist features abrasive and chemicalresistant powder coating, comes with all fasteners, mounting and body prop hardware and is covered under a 3-year product warranty.



Lifting Capacities: 8 - 18TONS

Body Length: 12-15 FT

Cylinder: 5"

Stroke: 20"

Conversion Class: D

Dump Class: 40

Mounting Height: 7 - 1/2"

Operation Pressure: 3000/1000 PSI

Subframe (If applicable)

Mounting Height: 7-1/2" Rail: 4"

ES/ED Power

Supply: Electric 12V DC

DM Power Supply: PTO

ES - 6 qt. reservoir

Hydraulic Req: ED - 4 qt. reservoir

PTO - 9 qt. reservoir

Weight:

VC520: 450 LBS **VC520** w/ **SF**: 570 LBS

PTO Pump: SAE "A" 2-bolt flange, 5/8" - 9 Spline (CCW Rot.) w/ 9 qt. reservoir

HOIST VC520

MAXIMUM LOAD CAPACITY CHART

Conversion Applications								
BODY	CA	ОН	40°(TON)	45° (TON)	50°(TON)			
12′	84"	30"	16.2	14.5	13.1			
13′	84"	42"	18.9	16.9	15.3			
13′	102"	24"	12.6	11.3	10.2			
13′	108"	18"	11.3	10.1	9.2			
14′	102"	36"	14.2	12.7	11.4			
14′	108"	30"	12.6	11.3	10.2			
14′	114"	24"	11.3	10.1	9.2			
14′	120″	18"	10.3	9.2	8.3			
14′	124″	14"	9.7	8.7	7.8			
14′	126″	12"	9.5	8.4	7.6			
15′	102"	48"	16.2	14.5	13.1			
15′	108"	42"	14.2	12.7	11.4			
15′	120″	30"	11.3	10.1	9.2			
15′	124″	26"	10.6	9.5	8.6			
15′	126″	24"	10.3	9.2	8.3			
15′	138″	12"	8.7	7.8	7.0			

Dump Body Applications								
BODY	CA	ОН	40°(TON)	45° (TON)	50°(TON)			
8′	-	12"	18.9	16.9	15.3			
9′	-	12"	16.2	14.5	13.1			
10′	-	12"	14.2	12.7	11.4			

ES/ED KITS

(ES) ELECTRIC-SINGLE ACTING PUMP

- Power-Up, Gravity Down
- 6 qt. Reservoir
- 12V DC Electric/Hydraulic Power Unit
- Includes Hoses, Controls, Hydraulic Fittings, Pump & Tank Combo

(ED) ELECTRIC-DOUBLE ACTING PUMP

- Power-Up, Power-Down
- 4 qt. Reservoir
- 12V DC Electric/Hydraulic Power Unit
- Includes Hoses, Controls, Hydraulic Fittings, Pump & Tank Combo

DM/LDK KITS

(DM) DIRECT-MOUNT PTO DRIVEN

- Power-Up, Power Down
- Pump: SAE "A" 2-bolt Flange, 5/8" 9 Spline Shaft CCW Rotation (9 qt reservoir)
- Includes Hoses, Controls, Hydraulic Fittings

(LDK) LESS DRIVE KIT

- INCLUDES: Mounting Kit, Rear Hinges & Scissors with Cylinder
- DOES NOT INCLUDE: Hoses, Controls, Hydraulic Fittings, Pump & Tank Combo

NOTE: Venco hoists are designed for and intended to be used on stationary trucks dumping on firm and level ground. Spreading applications and/or shock unloading are strictly prohibited and will void any warranty. Copyright © 2024 Venco Venturo Industries LLC. All Rights Reserved.

